

MAN (GV 23.5/33ATL)

ITEM	PART NO.	中文名称	ENGLISH DESCRIPTION
1	055-2-1058	进阀座96.15X85X18	INLET VALVE SEAT 96.15X85X18 MAN GV23.5/33ATL
2	113-01-1001 φ93Xφ 18.8X314	进气阀	INLET VALVE CONE
3	113-01-1001 φ97Xφ 18.8X314	进气阀	INTAKE VAVLE
4	113-1-1002	阀导筒	IN/OUT VALVE GUIDE
5	114-1-1033 φ93Xφ 18.8X314	排气阀	EXHAUST VALVE
6	114-1-1033 φ97Xφ 18.8X314	排气阀	EXHAUST VAVLE
7	23.5/33A-MAIN BEARING SHELLS U/S 1.00MM D-159MM	主轴瓦 加厚1MM	MAIN BEARING U/S 1.00MM D=159MM
8	23.5/33A-MAIN THRUST BEARING SHELLS U/S 1.00MM D=159MM	推力瓦 加厚1MM	MAIN THRUST BEARING SHELL U/S 1.00MM D=159MM
9	6GV 23.5/33A-021-1007	主轴瓦	MAIN BEARING
10	6GV 23.5/33A-MAIN BEARING	主轴瓦	MAIN BEARING
11	6GV 23.5/33-CON ROD BAERING STD BORE DIA:152mm	连杆瓦DIA:152mm	CON ROD BEARING STD BORE DIA:152mm
12	6GV 23.5/33-CON ROD BEARING U/S 1.00MM D=159MM	连杆瓦	CON ROD BEARING U/S 1.00MM D=151MM
13	6GV 23.5/33-CON ROD BEARING U/S 2.00MM D=158MM	连杆瓦	CON ROD BEARING U/S 2.00MM D=150MM
14	6GV 23.5/33-MAIN BEARING U/S 2.00MM D=158MM	主轴瓦	MAIN BEARING U/S 2.00MM D=158MM
15	6GV 23.5/33-THRUST BEARING U/S 2.00MM D=158MM	推力瓦	THRUST BEARING U/S 2.00MM D=158MM
16	EXHAUST VALVE 23.5/33ATL	排气阀	EXHAUST VALVE
17	GV23.5/33A-1003	缸盖垫片	CYLINDER HEAD COPPER
18	GV23.5/33A-1092&1093	油嘴	FUEL VALVE NOZZLE
19	GV23.5/33A-1099	NOZZLE CAP GROUP	NOZZLE CAP GROUP

20	GV23.5/33ATL-1003	连杆瓦	CONN ROD BEARING SHELL DIA 159
21	GV23.5/33ATL-1007	主轴瓦	BEARING HALVES DIA158
22	GV23.5/33ATL-1008	推力瓦	BEARING HALVES DIA158
23	INLET VALVE SEAT 96.15X85X18	进阀座96.15X85X18	INLET VALVE SEAT 96.15X85X18 MAN GV23.5/33ATL
24	MAN GV23.5/33 CON.ROD BEARING	连杆瓦	CON ROD BEARING
25	MAN GV23.5/33 MAIN BEARING	主轴瓦	MAIN BEARING
26	OUTLET VALVE SEAT 89.5X105X9	排阀座89.5X105X9.5	OUTLET VALVE SEAT 89.5X105X9.5
27	OUTLET VALVE SEAT 96X84X8	排阀座96X84X8	OUTLET VALVE SEAT 96X84X8
28	T50070	进阀座96.15X85X18	INLET VALVE SEAT 96.15X85X18 MAN GV23.5/33ATL
29	VALVE GUIDE GV23.5/33ATL	阀导筒	IN/OUT VALVE GUIDE

[CATALOGUE](#)